

**NIPPON WEATHERBOND ADVANCE**

<b>DESCRIPTION</b>	:	Nippon Weatherbond Advance is specially formulated for exterior walls exposed to harsh sunlight and extreme weather conditions. It has innovative "sunblocked technology" that reduces surfaces temperature and making the interiors of the house cooler. It possesses tough paint film, low VOC and high dirt pick up resistance. It's Anti-Algal and Anti-fungal property helps keep your facades looking newer for longer.
<b>TYPE</b>	:	Acrylic emulsion for exterior use
<b>COLOUR</b>	:	Wide range of colours
<b>FINISH</b>	:	Mid Sheen
<b>USES</b>	:	Suitable for new and previously painted surfaces such as masonry, bricks and exterior walls .
<b>FEATURES</b>	:	<ul style="list-style-type: none"><li>• Enhanced resistance to fungal and algal growth</li><li>• Enhanced anti-streak marks property keeping the façade clean</li><li>• Excellent weather durability under local climatic conditions</li><li>• Good adhesion on stable surfaces</li><li>• Easy application with good levelling property</li><li>• Excellent anti-carbonation property</li><li>• High water vapour permeability</li><li>• Environmentally friendly paint certified under the Singapore Green Labeling Scheme SGL-032 by the Singapore Environment Council with V.O.C. level less than 50g/L</li></ul>
<b>APPLICATION DATA</b>		
<b>METHOD</b>	:	Roller or brush
<b>THEORETICAL COVERAGE</b>	:	Approx. 16 -18 m <sup>2</sup> / litre (based on 40 microns DFT) Actual coverage will depend on the surface texture & application method.
<b>DILUTION</b>	:	30- 40% with clean water
<b>SURFACE PREPARATION</b>	:	Ensure surface is clean, dry and stable. Remove loose surface matter and contaminants by appropriate means. Treat fungus growth areas with NIPPON ANTI-FUNGUS SOLUTION.

**NIPPON WEATHERBOND ADVANCE**

<b>DRYING TIME</b>	:	Surface Dry - 30 minutes at 30 °C Hard Dry - 1 hour at 30 °C
<b>OVERCOATING TIME</b>	:	2 hours based on normal conditions
<b>RECOMMENDED PAINTING SYSTEM</b>	:	1 coat of Nippon Vinilex 2000 Wall Sealer 2 coats of Nippon Weatherbond Advance
<b>CLEANING</b>	:	All equipment should be cleaned with water immediately after use.
<b>GENERAL INFORMATION</b>		
<b>SOLID CONTENT</b>	:	55.0 ± 2% by weight (based on white colour)
<b>SPECIFIC GRAVITY</b>	:	1.35 ± 2% (based on white colour)
<b>PACKING</b>	:	1- litre, 5-litre, 10 - litre and 20-litre
<b>STORAGE</b>	:	Store in a tightly sealed container in a cool dry place.
<b>SHELF LIFE</b>	:	Up to 2 years in a tightly sealed container.
<b>PRECAUTION</b>	:	Ensure good ventilation during application and drying of paint. Avoid direct contact with sensitive skin. Use appropriate personal protective equipment. Refer to the product Safety Data Sheet for more information.

The information given is intended to give a description of the product performance under specific test conditions. Nevertheless, we cannot assume any responsibility for the use of it since circumstances under which the products are applied in practice are subjected to many variations. We reserve the right to alter the given data without notice.

<b>Enquiries / Contact Details</b>	:	<b>Nippon Paint Lanka (Pvt) Ltd.</b> <b>Nippolac Towers,</b> <b>69A, Buthgamuwa Road,</b> <b>Rajagiriya,</b> <b>Sri Lanka.</b> <b>Phone +94-114-600400</b> <b>Fax +94-112-600409</b> <b>E-mail: colombo@nipponpaint.com.lk</b> <b>Web : www.nipponpaint.lk</b>
------------------------------------	---	--